## RMC1110-640-HS

- ♠ MB spec: 12" x 13" & below.
- \$ 12Gb/s passive BP. Fits SAS3.0/SATA3.0 Drive.
- Single power or 1+1 redundant PSU.
- ♦ Intelligent thermal control, up to 6x 4056 hot-swap fans.



















## **Tech Parameters**

Basic Parameters	Chassis Form	Rackmount
	Chassis Height	10
	Motherboard Adapted	EEB(12*13)/CEB(12*10.5)/ATX(12*9.5)/Micro ATX
	Power Type	Single power or 1+1 redundant power supply
	Backplane	12Gb/s passive backplane
	Hard Drive Bay	Supports SGPIO; compatible with SAS3.0/SATA3.0 hard drive, 10* 2.5" hot-swap hard drive bays
	Shockproof Hard Drive	The hard drive rack adopts EMI spring design, unique shockproof fan design, reduces the resonance between the fan and the hard disk, and does not affect the hard drive I/O speed
	* Heat Dissipation	Supports intelligent-temperature control, 5x 4028 hot-swap fans, up to 6x 4056 fans
	Expansion Slot	1 full-height PCIe expansion card slot
	Front Panel Controls	2 USB2.0, 1 power button, 1 restart button, 1 hard disk indicator, 1 system fault indicator, 2 network indicators
	Slide Rails	Optional
	Air Duct	Optional
Shape Spec	Material	Imported SGCC (galvanized steel sheet), ABS panel and perforated mesh
	Widterial	——————————————————————————————————————
	Dimensions	640*433*43.5mm (D* W* H)
	Weight	7.2kg (Net weight) / 9.5kg (Gross weight)
	Packaging Size	902mm*591mm*183mm(D* W* H)
	Certification	CE, FCC, RoHS2.0





