


## RMC2112-670-HS/HSE

- ☞ MB spec: 12" x 13" & below.
- ☞ 12Gb/s BP. Fits SAS3.0/SATA3.0 Drive.
- ☞ Single power or 1+1 redundant PSU.
- ☞ Intelligent thermal control, up to 4x 8038 hot-swap fans.



## Tech Parameters

Basic Parameters	Model	RMC2112-670-HS	RMC2112-670-HSE
	Chassis Form	Rackmount	
	Chassis Height	2U	
	Motherboard Adapted	EEB(12*13)/CEB(12*10.5)/ATX(12*9.5)/Micro ATX	
	Power Type	Single power or 1+1 redundant power supply	
	Backplane	12Gb/s passive backplane	12Gb/s active backplane
	Hard Drive Bay	Supports SGPIO; compatible with SAS3.0/SATA3.0 hard drive; 12x 3.5" (or 2.5") hot-swap hard drive bays; optional rear 2* 2.5" hot-swap hard drives	
	Shockproof Hard Drive	The hard drive rack adopts EMI spring design, unique shockproof fan design, reduces the resonance between the fan and the hard disk, and does not affect the hard drive I/O speed	
	Heat Dissipation	Supports intelligent-temperature control, 3x 8038 hot-swap fans, up to 4x 8038 hot-swap fans	
	Expansion Slot	7x half-height PCIe expansion card slots, optional 3x horizontal full-height expansion card slots	
Shape Spec	Front Panel Controls	2 USB2.0, 1 power button, 1 restart button, 1 hard disk indicator, 1 system fault indicator, 2 network indicators	
	Slide Rails	Optional	
	Air Duct	Optional	
	Material	Imported SGCC (galvanized steel sheet), ABS panel and perforated mesh	
	Dimensions	670*444*87.6mm (D* W* H)	
	Weight	10.5kg (Net weight) / 16kg (Gross weight)	
	Packaging Size	902mm*591mm*228mm (D* W* H)	
Certification	CE, FCC, RoHS2.0		

