

# 4U SERVER CHASSIS

 The 4th GEN Server Chassis

## RMC4124-670-HS/HSE

- ☉ MB spec: 12" x 13" & below.
- ☉ 12Gb/s BP. Fits SAS3.0/SATA3.0 Drive.
- ☉ Single power or 1+1 redundant PSU.
- ☉ Intelligent thermal control, up to 3x 12038 hot-swap fans.



## Tech Parameters

Basic Parameters	Model	RMC4124-670-HS	RMC4124-670-HSE
	Chassis Form	Rackmount	
	Chassis Height	4U	
	Motherboard Adapted	EEB(12*13)/CEB(12*10.5)/ATX(12*9.5)/Micro ATX	
	Power Type	Single power or 1+1 redundant power supply	
	Backplane	12Gb/s passive backplane	12Gb/s active backplane
	Hard Drive Bay	Supports SGPIO; compatible with SAS3.0/SATA3.0 hard drive; 24x 3.5" (or 2.5") hot-swap hard drive bays; 2x 2.5" built-in non-hot-swap hard drive bays; optional 2x 2.5" rear hot-swap hard drives	
	Shockproof Hard Drive	The hard drive rack adopts EMI spring design, unique shockproof fan design, reduces the resonance between the fan and the hard disk, and does not affect the hard drive I/O speed	
	Heat Dissipation	Supports intelligent-temperature control, 3x 12038 hot-swap fans	
	Expansion Slot	7x full-height PCIe expansion card slots	
	Front Panel Controls	2 USB2.0, 1 power button, 1 restart button, 1 hard disk indicator, 1 system fault indicator, 2 network indicators	
	Slide Rails	Optional	
	Air Duct	Optional	
Shape Spec	Material	Imported SGCC (galvanized steel sheet), ABS panel and perforated mesh	
	Dimensions	670*444*177mm (D* W* H)	
	Weight	18kg (Net weight) / 24kg (Gross weight)	
	Packaging Size	902mm*591mm*318mm (D* W* H)	
	Certification	CE, FCC, RoHS2.0	

