

AMD Genoa Dual-Socket High-End Server



SR201-D08R-G2



SR201-D12RE-G2

Front hard drive	Up to 8x 3.5"/2.5" SAS/SATA/NVMe hot-swap hard drives
Rear hard drive	Rear optional 2x 2x2.5" SAS/SATA/NVMe hard drives
Processor	Supports two AMD EPYC 9004 (Genoa) processors
Memory	24 DDR5 memory slots, support 4800, 4400 DDR5 RDIMM memory
Storage controllers	Onboard 3 MiniSAS SFF-8643 connectors, 2 SATA interfaces, 2 SATA DOM interfaces, 2 M.2 interfaces (PCIe5.0 X4 signal, 2280), 2 slimlinux8 (PCIe4.0 x8 signal) interfaces
Driver	Supports 8 hot-swap SAS/SATA (HDD/SSD)
Power	Support 800W/1300W/1600W/2000W/2200W hot-swap redundant power (adapt according to the actual power)
External port & PCIe	Front: 1 VGA, 2 USB3.0 Rear: 1 VGA, 1 COM port, 2 USB3.0, 1 RJ45 Gigabit management network port, 2 Gigabit RJ45 network ports PCIe extended form: Riser1/Riser2: 2x PCIe5.0 x16 Riser3: 2x PCIe5.0 x8 Riser4: 1x PCIe4.0 x16 or 2x PCIe4.0 x8
Intelligent temp. control	Supports
Fan	Standard 4x 8038 hot-swap fans, optional 4x 8056 hot-swap redundant fans
Network	2x 1GbE (RJ45) onboard
Security	TPM/TCM (optional) Chassis open intrusion detection Locked upper cover of chassis
Management	1 dedicated RJ45 management network port IPMI2.0
OS	Microsoft Windows Server、Red Hat Enterprise Linux、SUSE Linux Enterprise Server、CentOS、Ubuntu
Virtualization	Citrix Xen Server、Vmware ESXi、Linux KVM、Windows Hyper-V
Certification	CCC、ROHS2.0
Size	748 x 433.4 x 87.6mm (D x W x H)
Temperature	Operating temperature: 5°C - 35°C (indoor) Storage temperature: -40°C - 70°C
Humidity	Operating humidity: 20% - 80% (non-condensing) Storage humidity: 20% - 90% (non-condensing)

Front hard drive	Up to 12x 3.5"/2.5" SAS/SATA/NVMe hot-swap hard drives
Rear hard drive	Rear optional 2x 2x2.5" SAS/SATA/NVMe hard drives
Processor	SSupports two AMD EPYC 9004 (Genoa) processors
Memory	24 DDR5 memory slots, support 4800, 4400 DDR5 RDIMM memory
Storage controllers	Onboard 3 MiniSAS SFF-8643 connectors, 2 SATA interfaces, 2 SATA DOM interfaces, 2 M.2 interfaces (PCIe5.0 X4 signal, 2280), 2 slimlinux8 (PCIe4.0 x8 signal) interfaces
Driver	Supports 12 hot-swap SAS/SATA (HDD/SSD)
Power	Support 800W/1300W/1600W/2000W/2200W hot-swap redundant power (adapt according to the actual power)
External port & PCIe	Front: 1 VGA, 2 USB3.0 Rear: 1 VGA, 1 COM port, 2 USB3.0, 1 RJ45 Gigabit management network port, 2 Gigabit RJ45 network ports PCIe extended form: Riser1/Riser2: 2x PCIe5.0 x16 Riser3: 2x PCIe5.0 x8 Riser4: 1x PCIe4.0 x16 or 2x PCIe4.0 x8
Intelligent temp. control	Supports
Fan	Standard 4x 8038 hot-swap fans, optional 4x 8056 hot-swap redundant fans
Network	2x 1GbE (RJ45) onboard
Security	TPM/TCM (optional) Chassis open intrusion detection Locked upper cover of chassis
Management	1 dedicated RJ45 management network port IPMI2.0
OS	Microsoft Windows Server、Red Hat Enterprise Linux、SUSE Linux Enterprise Server、CentOS、Ubuntu
Virtualization	Citrix Xen Server、Vmware ESXi、Linux KVM、Windows Hyper-V
Certification	CCC、ROHS2.0
Size	748 x 433.4 x 87.6mm (D x W x H)
Temperature	Operating temperature: 5°C - 35°C (indoor) Storage temperature: -40°C - 70°C
Humidity	Operating humidity: 20% - 80% (non-condensing) Storage humidity: 20% - 90% (non-condensing)