

AMD Milan Dual-Socket High-End Server



SR401-D24RE



SR401-D36RE

Front hard drive	Up to 24x 3.5"/2.5" SAS/SATA3.0 hot-swap hard drives
Rear hard drive	Optional 4x 3.5" SAS/SATA or 4x 2.5" SAS/SATA/U.2 hard drives
Processor	Supports 1 or 2 AMD EPYC 7003 series, compatible with AMD EPYC 7002 & 7001 series
Memory	32 DDR4 slots, support 2666/2933/3200MHz DDR4 memory
Storage controllers	2 PCIe 4.0/3.0 x 2 M.2 ports 4 SATA 7PIN slots (2 of them support SATA DOM) 3 MiniSAS HD ports
Driver	Supports 24 hot-swap SAS/SATA (HDD/SSD)
Power	Support 550W, 800W, 1300W, 1600W, 2200W redundant power supply (adapt according to the actual power)
External port & PCIe	Front Port: 2 USB3.0 Rear: 1 VGA, 1 COM port, 2 USB3.0, 1 management network port, 2 RJ45 network ports PCIe expansion slots: 6 PCIe full-height slots, 4 PCIe half-height slots OCP slot: 1 PCIe 3.0 x8
Intelligent temp. control	Supports
Fan	Standard 8x 8038 hot-swap fans
Network	2x 1GbE (RJ45) onboard
Security	TPM/TCM (optional) Chassis open intrusion detection Locked upper cover of chassis
Management	1 dedicated RJ45 management network port IPMI2.0
OS	Microsoft Windows Server、Red Hat Enterprise Linux、SUSE Linux Enterprise Server、CentOS、Ubuntu
Virtualization	Citrix Xen Server、Vmware ESXi、Linux KVM、Windows Hyper-V
Certification	CCC
Size	798 x 433.4 x 176.5mm (D x W x H)
Temperature	Operating temperature: 5°C - 35°C (indoor) Storage temperature: -40°C - 70°C
Humidity	Operating humidity: 20% - 80% (non-condensing) Storage humidity: 20% - 90% (non-condensing)

Up to 36x 3.5"/2.5" SAS/SATA3.0 hot-swap hard drives
Optional 4x 3.5" SAS/SATA or 4x 2.5" SAS/SATA/U.2 hard drives
Supports 1 or 2 AMD EPYC 7003 series, compatible with AMD EPYC 7002 & 7001 series
32 DDR4 slots, support 2666/2933/3200MHz DDR4 memory
2 PCIe 4.0/3.0 x 2 M.2 ports 4 SATA 7PIN slots (2 of them support SATA DOM) 3 MiniSAS HD ports
Supports 36 hot-swap SAS/SATA (HDD/SSD)
Support 550W, 800W, 1300W, 1600W, 2200W redundant power supply (adapt according to the actual power)
Front Port: 2 USB3.0 Rear: 1 VGA, 1 COM port, 2 USB3.0, 1 management network port, 2 RJ45 network ports PCIe expansion slots: 6 PCIe full-height slots, 4 PCIe half-height slots OCP slot: 1 PCIe 3.0 x8
Supports
Standard 8x 8038 hot-swap fans
2x 1GbE (RJ45) onboard
TPM/TCM (optional) Chassis open intrusion detection Locked upper cover of chassis
1 dedicated RJ45 management network port IPMI2.0
Microsoft Windows Server、Red Hat Enterprise Linux、SUSE Linux Enterprise Server、CentOS、Ubuntu
Citrix Xen Server、Vmware ESXi、Linux KVM、Windows Hyper-V
CCC
798 x 433.4 x 176.5mm (D x W x H)
Operating temperature: 5°C - 35°C (indoor) Storage temperature: -40°C - 70°C
Operating humidity: 20% - 80% (non-condensing) Storage humidity: 20% - 90% (non-condensing)