

INTEL Eagle Stream Dual-Socket High-end Serve



SL201-D08R-G4



SL201-D12R/-NV-G4

Front hard drive	Up to 8x 3.5"/2.5" SAS/SATA hot swap hard drives
Rear hard drive	Supports 2x 2x 3.5-inch hard drive modules or 2x 2x 2.5-inch hard drive modules
Processor	Supports 1 or 2 4th Generation Intel® Xeon® Scalable Processors, TDP up to 350W
Chipset	Intel® C741 series dedicated processor chipset
Memory	32 DDR5 memory slots, support DDR5 LRDIMM/RDIMM 4400/4800MHz
Storage controllers	3 mini SAS HD interface , 2 SATA M.2 SSD interfaces
Driver	Support 8 hot-swap SAS/SATA(HDD/SSD)
Power	AC supports 220V 800W, 1300W, 1600W, 2000W, 2200W, 2600W redundant power supply(according to actual power adaptation)
External port & PCIe	Front ports: 1 VGA, 2 USB3.0 Rear ports: 1 VGA, 1 COM port, 2 USB3.1, 1 RJ45 Gigabit management network port 6x PCIe full height slots, 4x PCIe half height slots, 2x OCP 3.0 slots Riser1/2: 1x full height PCIe 5.0 x16, 2x full height PCIe 5.0 x8, 2x full height PCIe 5.0 x16 Riser3/4 : 2x half-height PCIe 5.0 x8, 1x half-height PCIe 5.0 x16 OCP: 2xOCP 3.0(PCIe 5.0x 8)
Intelligent temp. control	Supports
Fan	Standard 4x 8056 hot-swap N+1 redundant fans
Network	2x OCP 3.0 network
Security	TPM/TCM (optional)
Management	1 dedicated RJ45 management network port IPMI 2.0
OS	Microsoft Windows Server、Red Hat Enterprise Linux、SUSE Linux Enterprise Server、CentOS、Ubuntu
Virtualization	Citrix Xen Server、Vmware ESXi、Linux KVM、Windows Hyper-V
Certification	CCC、CE、FCC、ROHS
Size	798.5 x 444.4 x 87.8mm (D x W x H)
Temperature	Operating temperature: 5°C - 35°C (indoor) Storage temperature: -40°C - 70°C
Humidity	Operating humidity: 20% - 80% (non-condensing) Storage humidity: 20% - 90% (non-condensing)

Front hard drive	Up to 12x 3.5"/2.5" SAS/SATA/U.2 hot swap hard drives
Rear hard drive	Supports 2x 2x 3.5-inch hard drive modules or 2x 2x 2.5-inch hard drive modules
Processor	Supports 1 or 2 4th Generation Intel® Xeon® Scalable Processors, TDP up to 350W
Chipset	Intel® C741 series dedicated processor chipset
Memory	32 DDR5 memory slots, support DDR5 LRDIMM/RDIMM 4400/4800MHz
Storage controllers	3 mini SAS HD interface , 2 SATA M.2 SSD interfaces
Driver	Support 12 hot-swap SAS/SATA/NVMe (HDD/SSD/U.2)
Power	AC supports 220V 800W, 1300W, 1600W, 2000W, 2200W, 2600W redundant power supply(according to actual power adaptation)
External port & PCIe	Front ports: 1 VGA, 2 USB3.0 Rear ports: 1 VGA, 1 COM port, 2 USB3.1, 1 RJ45 Gigabit management network port 6x PCIe full height slots, 4x PCIe half height slots, 2x OCP 3.0 slots Riser1/2: 1x full height PCIe 5.0 x16, 2x full height PCIe 5.0 x8, 2x full height PCIe 5.0 x16 Riser3/4 : 2x half-height PCIe 5.0 x8, 1x half-height PCIe 5.0 x16 OCP: 2xOCP 3.0(PCIe 5.0x 8)
Intelligent temp. control	Supports
Fan	Standard 4x 8056 hot-swap N+1 redundant fans
Network	2x OCP 3.0 network
Security	TPM/TCM (optional)
Management	1 dedicated RJ45 management network port IPMI 2.0
OS	Microsoft Windows Server、Red Hat Enterprise Linux、SUSE Linux Enterprise Server、CentOS、Ubuntu
Virtualization	Citrix Xen Server、Vmware ESXi、Linux KVM、Windows Hyper-V
Certification	CCC、CE、FCC、ROHS
Size	798.5 x 444.4 x 87.8mm (D x W x H)
Temperature	Operating temperature: 5°C - 35°C (indoor) Storage temperature: -40°C - 70°C
Humidity	Operating humidity: 20% - 80% (non-condensing) Storage humidity: 20% - 90% (non-condensing)

Please note that the above specifications are subject to change without prior notice. (Gooxi reserves the right for the final interpretation)