

Intel Eagle Stream Dual-Socket AI Server



■ AS4110G-G4

- >> 1/2 4th Gen or 5th Gen Intel® Xeon® Scalable processor
- >> Supports 16 DDR5 4400/4800/5600MHz ECC memory slots
- >> The whole machine supports up to 19 PCIe expansion slots
- » Supports CPU-GPU switch expansion mode
- >> Up to 10x 600W Dual-Width GPU cards
- » Suitable for cloud computing, virtualization, big data analysis, digital twin, deep learning and other application scenarios







System Model	AS4110G-D04R-G4
Product Type	4U 10-GPU 4-bay
Front Hard Drive	Up to 4 hot-swappable 3.5/2.5" SATA/SAS hard drives
Rear Hard Drive	4x 2.5" SATA/SAS or 4 U.2 hard drives
Processor	Supports 1/2 4th Gen or 5th Gen Intel® Xeon® Scalable processor , TDP supports up to 350W
GPU	Supports up to 10x 600W dual-width GPUs
Memory	16 DDR5 memory slots, supporting DDR5 4400/4800/5600MHz
Storage Interface	3 SlimSAS interfaces (SFF8643), 2*2280/22110 size M.2 (NVMe)
Power Supply	3+1 redundancy (2000W/2200W/2600W/3200W)
External Port & PCIe	External Ports Front: 2x USB 3.0, 1x VGA Rear: 1 serial port, 2 USB 3.0 ports, 2 USB 2.0 ports, 1 VGA, 1 RJ45 management port, 2 RJ45 gigabit Ethernet ports PCIe Expansion Rear PCIe Slot: 5x full-length half-height single-width, supporting up to 9x full-length half-height single-width Front PCIe Slot: 10x full-length full-height double-width
Fan	11 standard hot-swappable 8038 fans
IPMI Compatibility	IPMI2.0
Security	Supports TPM2.0 module
Management	1 dedicated RJ45 management port
OS	Microsoft Windows Server、Red Hat Enterprise Linux、SUSE Linux Enterprise Server、CentOS、Ubuntu
Virtualization	Citrix Xen Server、Vmware ESXi、Linux KVM、Windows Hyper-V
Size	850mm x 433mm x 176.5mm (D x W x H)
Temperature	Operating temperature: 5°C - 35°C (indoor); Storage temperature: -40°C - 70°C
Humidity	Operating humidity: 20% - 80% (non-condensing); Storage humidity: 20% - 90% (non-condensing)