

INTEL Eagle Stream Dual-Socket High-end Serve

SL401-G4



4U36 SATA/SAS Expansion

SL401-D36RE-G4

Front hard drive	Up to 24x 3.5"/2.5" SAS/SATA hot swap hard drives
Rear hard drive	12x 3.5" SATA/SAS hot swap hard drives,optional 2x 2x 2.5" SATA/SAS or U.2 hard drive modules
Processor	Supports 1 or 2 4th/5th Generation Intel® Xeon® Scalable Processors , TDP up to 350W
Chipset	Intel® C741 series dedicated processor chipset
Memory	32 DDR5 memory slots, supports DDR5 RDIMM 4400/4800/5600MHz
Storage controllers	3 Mini SAS HD interfaces, 2 SATA M.2 SSD interfaces (optional 2 NVMe M.2 SSD), 14 MCIO interfaces
Driver	Supports 36 hot-swap SAS/SATA (HDD/SSD)
Power	AC supports 220V 800W, 1300W, 1600W, 2000W, 2200W, 2600W redundant power supply (according to actual power adaptation)
External port & PCIe	Front:1 VGA, 2 USB3.0 Rear: 1x VGA, 1x COM port, 2x USB3.0, 1x RJ45 Gigabit management network port 6x PCIe full-height slots, 4x PCIe half-height slots, 2x OCP 3.0 slots Riser1/2: 1x full-height PCIe 5.0 x16 + 2x full-height PCIe 5.0x8 or 2x full-height PCIe 5.0 x16 Riser3/4: 2x half height PCIe 5.0 x8 or 1x half height PCIe 5.0x16 OCP: 2xOCP 3.0(Pcie 5.0 x8)
Intelligent temp. control	Support
Fan	Standard 8 hot-swappable N+1 redundant fans, supporting 8038/8056 specifications
IPMI	Supports standard interfaces such as Redfish, SNMP, and IPMI 2.0
Security	Supports TPM 2.0 module, chassis intrusion alert, BMC/BIOS redundancy
Management	1 dedicated RJ45 management network port
OS	Microsoft Windows Server、Red Hat Enterprise Linux、SUSE Linux Enterprise Server、CentOS、Ubuntu
Virtualization	Citrix Xen Server、Vmware ESXi、Linux KVM、Windows Hyper-V
Certification	CCC、CE、FCC、ROHS
Size	830 x 444 x 176.5mm (D x W x H)
Temperature	Operating temperature: 5°C - 35°C (indoor) Storage temperature: -40°C - 70°C
Humidity	Operating humidity: 20% - 80% (non-condensing) Storage humidity: 20% - 90% (non-condensing)

AMD Genoa Dual-Socket High-End Server

SR201-G2



2U8 SATA/SAS Direct Connection

SR201-D08R-G2

2U8 NVMe Direct Connection

SR201-D08R-NV-G2

Front hard drive	Up to 8x 3.5"/2.5" SAS/SATA hot-swap hard drives
Rear hard drive	Rear optional 2x 2×2.5" SAS/SATA/NVMe hard drives
Processor	Supports 1 or 2 AMD EPYC 9004 (Genoa) processors
Memory	24 DDR5 memory slots, supports 4800/4400 DDR5 RDIMM memory
Storage controllers	Onboard 3 MiniSAS SFF-8643 connectors, 2 SATA interfaces, 2 M.2 interfaces (PCIe X4 signal, 2280), 2 slimline x8 (PCIe4.0 x8 signal) interfaces
Driver	Supports 8 hot-swap SAS/SATA(HDD/SSD)
Power	Supports 800W/1300W/1600W/2000W/2200W hot-swap redundant power (adapt according to the actual power)
External port & PCIe	Front: 1 VGA, 2 USB3.0 Rear: 1 VGA, 1 COM port, 2 USB3.0, 1 RJ45 Gigabit management network port, 2 Gigabit RJ45 network ports PCIe extended form: Riser1/Riser2: 2x PCIe5.0 x16 or 1x PCIe5.0 x16+2x PCIe5.0 x8 Riser3: 2x PCIe5.0 x8 or1x PCIe5.0 x16 Riser4: 1x PCIe4.0 x16 or 2x PCIe3.0 x8
Intelligent temp. control	Support
Fan	Standard 4x 8038 hot-swap fans, optional 4x 8056 hot-swap redundant fans (Supports Max TDP of 400W)
Network	2x 1GbE (RJ45) onboard
Security	TPM/TCM (optional) Chassis open intrusion detection Locked upper cover of chassis
Management	1 dedicated RJ45 management network port IPMI2.0
OS	Microsoft Windows Server、Red Hat Enterprise Linux、SUSE Linux Enterprise Server、CentOS、Ubuntu
Virtualization	Citrix Xen Server、Vmware ESXi、Linux KVM、Windows Hyper-V
Certification	CCC、ROHS2.0
Size	748 x 433.4 x 87.6mm (D x W x H)
Temperature	Operating temperature: 5°C - 35°C (indoor) Storage temperature: -40°C - 70°C
Humidity	Operating humidity: 20% - 80% (non-condensing) Storage humidity: 20% - 90% (non-condensing)

Up to 8x 3.5"/2.5" SAS/SATA/NVMe hot-swap hard drives
Rear optional 2x 2×2.5" SAS/SATA/NVMe hard drives
Supports 1 or 2 AMD EPYC 9004 (Genoa) processors
24 DDR5 memory slots, supports 4800, 4400 DDR5 RDIMM memory
Onboard 3 MiniSAS SFF-8643 connectors, 2 SATA interfaces, 2 M.2 interfaces (PCIe X4 signal, 2280), 2 slimline x8 (PCIe4.0 x8 signal) interfaces
Supports 8 hot-swap SAS/SATA/NVMe(HDD/SSD/U.2)
Supports 800W/1300W/1600W/2000W/2200W hot-swap redundant power (adapt according to the actual power)
Front: 1 VGA, 2 USB3.0 Rear: 1 VGA, 1 COM port, 2 USB3.0, 1 RJ45 Gigabit management network port, 2 Gigabit RJ45 network ports PCIe extended form: Riser1/Riser2: 2x PCIe5.0 x16 or 1x PCIe5.0 x16+2x PCIe5.0 x8 Riser3: 2x PCIe5.0 x8 or1x PCIe5.0 x16 Riser4: 1x PCIe4.0 x16 or 2x PCIe3.0 x8
Support
Standard 4x 8038 hot-swap fans, optional 4x 8056 hot-swap redundant fans (Supports Max TDP of 400W)
2x 1GbE (RJ45) onboard
TPM/TCM (optional) Chassis open intrusion detection Locked upper cover of chassis
1 dedicated RJ45 management network port IPMI2.0
Microsoft Windows Server、Red Hat Enterprise Linux、SUSE Linux Enterprise Server、CentOS、Ubuntu
Citrix Xen Server、Vmware ESXi、Linux KVM、Windows Hyper-V
CCC、ROHS2.0
748 x 433.4 x 87.6mm (D x W x H)
Operating temperature: 5°C - 35°C (indoor) Storage temperature: -40°C - 70°C
Operating humidity: 20% - 80% (non-condensing) Storage humidity: 20% - 90% (non-condensing)